



PAKTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	BLACK	1
B CONTACT	BRONZE	BRIGHT TIN PLATED	9

DONGGUAN CHANGJUN ELECTRONICS CO., LTD 东莞市昌骏电子有限公司	
TITLE: 空焊针脚插头	
TOLERANCE	±0.05
.xxx	±0.10
.xx	±0.20
.x	±0.50
ANGLE	±1°
PART NO:	CJ-BMS-F01
SHEET:	1 / 1
DRAWN:	Xie Wenjun
CHECKS:	Long Jichang
DATE:	2022-01-05
DRAWING NO.:	CP-BM0019
UNIT:	mm
SCALE:	1 : 1
SIZE:	A4
REV:	A/0

Engagement force	Rated voltage	Rated current	Rated voltage
≤60N	24V	2A	24V
Disengagement force	Rated current	Rated voltage	Rated current
≥35N	2A	24V	2A
Mechanical lifespan	Insulation resistance	Rated current	Rated voltage
≥500	≥1000MΩ	2A	24V
IP rating	Contact resistance	Rated current	Rated voltage
	≤10mΩ	2A	24V
Flammability	Operation Temperature	Rated current	Rated voltage
UL94 V-0	-25° C~85° C	2A	24V