



Engagement force	$\leq 38\text{N}$	Rated voltage	24V
Disengagement force	$\geq 20\text{N}$	Rated current	2A
Mechanical lifespan	≥ 500	Insulation resistance	$\geq 1000\text{M}\Omega$
IP rating		Contact resistance	$\leq 10\text{m}\Omega$
Flammability	UL94 V-0	Operation Temperature	$-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	BLACK	1
B CONTACT	BRONZE	BRIGHT TIN PLATED	5

Dongguan Changjun Electronics Co., Ltd 东莞市昌骏电子有限公司		TITLE: 宝马连接器插头 (大规格)	
TOLERANCE .xxx ±0.05 .xx ±0.10 .x ±0.20 ANGLES ±1°		PART NO: CJ-BMS-F11 DRAWING NO.: GP-BM0011	
SHEET: 1 / 1 DRAWN: Xie Wenjun CHECKS: Long Jichang DATE: 2022-01-05		SCALE: 1 : 1 UNIT: mm SIZE: REV A/0	

由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作

1

2

3

4

5

6

7

8

由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作