



| PARTS | MATERIALS | TREATMENT | AMOUNT |
|-----------|-----------|---------------|--------|
| A HOUSING | PA66+GF | BLACK | 1 |
| B CONTACT | BRASS | SILVER PLATED | 5 |

| | |
|---|--|
| DONGGUAN CHANGJUN ELECTRONICS CO., LTD 东莞市昌骏电子有限公司 | |
| TITLE: 宝马磁螺线管公头(小新款) PART NO.: CJ-BMG-M01 DRAWING NO.: GP-BMG008 | |
| TOLERANCE: .xxx ±0.05 .xx ±0.10 .x ±0.20 x ±0.50 ANGLE ±1° | SHEET: 1 / 1 SCALE: 1 : 1 UNIT: mm SIZE: A4 REV: A/0 |
| DRAWN: Xie Wenjun CHECKS: Long Jichang DATE: 2022-01-05 | |

| Engagement force | Rated voltage | Rated current |
|---------------------|-----------------------|--------------------|
| ≤38N | 24V | 2A |
| Disengagement force | Insulation resistance | Contact resistance |
| ≥20N | ≥1000MΩ | ≤10mΩ |
| Mechanical lifespan | Operation Temperature | |
| ≥500 | -25° C~85° C | |
| IP rating | | |
| Flammability | UL94 V-0 | |

| Engagement force | Rated voltage | Rated current |
|---------------------|-----------------------|--------------------|
| ≤38N | 24V | 2A |
| Disengagement force | Insulation resistance | Contact resistance |
| ≥20N | ≥1000MΩ | ≤10mΩ |
| Mechanical lifespan | Operation Temperature | |
| ≥500 | -25° C~85° C | |
| IP rating | | |
| Flammability | UL94 V-0 | |

| Engagement force | Rated voltage | Rated current |
|---------------------|-----------------------|--------------------|
| ≤38N | 24V | 2A |
| Disengagement force | Insulation resistance | Contact resistance |
| ≥20N | ≥1000MΩ | ≤10mΩ |
| Mechanical lifespan | Operation Temperature | |
| ≥500 | -25° C~85° C | |
| IP rating | | |
| Flammability | UL94 V-0 | |

| Engagement force | Rated voltage | Rated current |
|---------------------|-----------------------|--------------------|
| ≤38N | 24V | 2A |
| Disengagement force | Insulation resistance | Contact resistance |
| ≥20N | ≥1000MΩ | ≤10mΩ |
| Mechanical lifespan | Operation Temperature | |
| ≥500 | -25° C~85° C | |
| IP rating | | |
| Flammability | UL94 V-0 | |