



A		B		C		D		E		F		G		H	
1		2		3		4		5		6		7		8	
Engagement force		≤35N		Rated voltage		pin 1 and 2 24V pin 3 24V		Rated current		pin 1 and 2 7.5A pin 3 1A		Disengagement force		≥35N	
Mechanical lifespan		≥1000		Insulation resistance		≥1000M Ω		Contact resistance		≤30m Ω		IP rating		UL94 V-0	
Flammability		UL94 V-0		Operation Temperature		-25° C~85° C		PARTS		MATERIALS		TREATMENT		AMOUNT	
								A HOUSING		PBT+GF		BLACK		1	
								B CONTACT		BRASS		SILVER PLATED		3	
								C OUTER CONTACT		BRASS		NICKEL PLATED		1	

Dongguan Changjun Electronics Co., Ltd
东莞市昌骏电子有限公司

TITLE: POWER DIN 3P公头 底座式

TOLERANCE	±0.05 ±0.10 ±0.20 ±0.50	PART NO:	CJ-PIG-M01	DRAWING NO.:	CP-POWER0011
ANGLE	±1°	SHEET:	1 / 1	UNITS:	mm
		SCALE:	1 : 1	SIZE:	A4
		DRAWN:	Xie Wenjun	CHECKS:	Long Jibang
		DATE:	2022-01-05	REV:	A/0