



PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PBT+GF	BLACK	1
B CONTACT	BRASS	SILVER PLATED	4
C OUTER CONTACT	BRASS	NICKEL PLATED	1+1
D PARTS	POM	BLACK	1
E SPRING	SS	BLACK	1
F SHELL	ABS	BLACK	1+1
G TAIL SLEEVE	PVC	BLACK	1

Dongguan Changjun Electronics Co., Ltd
东莞市昌骏电子有限公司

TITLE: POWER DIN 4芯头 单瓣头八件套装
 TOLERANCE: ±0.05
 ±0.10
 ±0.20
 ±0.50
 ANGLES: ±1°

PART NO: CJ-PD4-M02A
 SHEET: 1 / 1
 SCALE: 1 : 1

DRAWING NO.: CJ-PWR0002
 UNIT: mm
 SIZE: A4
 REV: A/0

DRAWN: Xie Wenjun
 CHECKED: Long Jibang
 DATE: 2022-01-05

Engagement force	Rated voltage	Rated current	Rated voltage
≤35N	24V	7.5A	24V
Disengagement force ≥35N			
Mechanical lifespan	Insulation resistance	Contact resistance	Operation Temperature
≥1000	≥1000MΩ	≤30mΩ	-25°C~85°C
IP rating	UL94 V-0		
Flammability	Operation Temperature		