



PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PBT+GF	BLACK	1
B CONTACT	BRASS	SILVER PLATED	4
C OUTER CONTACT	BRASS	NICKEL PLATED	1

Dongguan Changjun Electronics Co., Ltd 东莞市昌骏电子有限公司	
TITLE:	POWER DIN 4E 公头 底座式
PART NO.:	CJ-PD4-M01
DRAWING NO.:	CP-POWER0012
SHEET:	1 / 1
SCALE:	1 : 1
UNIT:	mm
SIZE:	A4
REV:	A/0
DRAWN:	Xie Wenjun
CHECK:	Long Jichang
DATE:	2022-01-05

Engagement force	Rated voltage	Rated current	Rated power
≤35N	24V	7.5A	180W
Disengagement force	Rated current	Rated power	Rated voltage
≥35N	7.5A	180W	24V
Mechanical lifespan	Insulation resistance	Contact resistance	Operation Temperature
≥1000	≥1000MΩ	≤30mΩ	-25° C~85° C
IP rating	Contact resistance	Operation Temperature	Flammability
UL94 V-0	≤30mΩ	-25° C~85° C	UL94 V-0

Engagement force	Rated voltage	Rated current	Rated power
≤35N	24V	7.5A	180W
Disengagement force	Rated current	Rated power	Rated voltage
≥35N	7.5A	180W	24V
Mechanical lifespan	Insulation resistance	Contact resistance	Operation Temperature
≥1000	≥1000MΩ	≤30mΩ	-25° C~85° C
IP rating	Contact resistance	Operation Temperature	Flammability
UL94 V-0	≤30mΩ	-25° C~85° C	UL94 V-0

Engagement force	Rated voltage	Rated current	Rated power
≤35N	24V	7.5A	180W
Disengagement force	Rated current	Rated power	Rated voltage
≥35N	7.5A	180W	24V
Mechanical lifespan	Insulation resistance	Contact resistance	Operation Temperature
≥1000	≥1000MΩ	≤30mΩ	-25° C~85° C
IP rating	Contact resistance	Operation Temperature	Flammability
UL94 V-0	≤30mΩ	-25° C~85° C	UL94 V-0