



由 Autodesk 教育版产品制作

PROPERTY	VALUE	PROPERTY	VALUE	PARTS	MATERIALS	TREATMENT	AMOUNT
Engagement force	≤25N	Dielectric Strength	>750V	HOUSING	PTFE	NATURAL COLOR	1
Disengagement force	≥5N	Rated voltage	350V/(rms)	CONTACT	BRASS	GOLD PLATED	1
Retention	≥110N	Frequency Range	DC to 6 GHz	OUTER CONTACT	BRASS	NICKEL PLATED	1
Mechanical lifespan	≥500	Voltage standing wave ratio	<1.30 (DC-3GHz)				
IP rating	IP67/IP68	Insulation resistance	<1.40 (3GHz-6GHz)				
Operation Temperature	-40° C~105° C	Contact resistance	≥1000V/Ω				
RF Leakage	≥65 dB	Insertion Loss	≤5m dB				

Dongguan Changjun Electronics Co., Ltd 东莞市昌俊电子有限公司			
TITLE: SMR公头 板端直头SMT		DRAWING NO.: CP-SMR0002	
PART NO.: CJ-SMR-M01	SCALE: 1:1	UNIT: mm	SIZE: REV A/0
SHEET: 1/1	DRAWN: Xie Wenjun	CHECKS: Long Jibang	DATE: 2022-01-05