



PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PTFE	NATURAL COLOR	1
B CONTACT	BRONZE	GOLD PLATED	1
C OUTER CONTACT	BRASS	NICKEL PLATED	1
D SHIELD	BRASS	NICKEL PLATED	1
E SHELL	PBT+GF	SPECIFY COLOR	1
F			

Engagement force	Dielectric Strength	Rated voltage	Frequency Range	Voltage standing wave ratio	Insulation resistance	Contact resistance	Insertion Loss
≤25N	>750V	350V/(rms)	DC to 6 GHz	<1.30 (DC-3GHz) <1.40 (3GHz-6GHz)	≥1000V/Ω	≤5mΩ	<0.1x√f (GHz) dB
Disengagement force	Rated voltage	Frequency Range	Voltage standing wave ratio	Insulation resistance	Contact resistance	Insertion Loss	
≥5N	≥110N	≥500	IP67/IP68	-40° C~105° C	≥65 dB		
Retention	Mechanical lifespan	IP rating	Operation Temperature	RF Leakage			
≥110N	≥500	IP67/IP68	-40° C~105° C	≥65 dB			

东莞市昌骏电子有限公司
Dongguan Changjun Electronics Co., Ltd

FAKRA公头 线端直头 (短体)

TITLE: FAKRA公头 线端直头 (短体)

PART NO: CJ-FAKRA-Z-M11

DRAWING NO.: CJ-FAKRA0003

SCALE: 1:1

UNIT: mm

SIZE: A4

REV: A/0

DATE: 2022-01-05

DRAWN: Xie Wenjun

CHECK: Long Jibang

由 Autodesk 教育版产品制作