



G		PARTS		MATERIALS		TREATMENT		AMOUNT	
Engagement force	≤25N	Dielectric Strength	>750V	A HOUSING	PTFE	NATURAL COLOR	1		
Disengagement force	≥5N	Rated voltage	350V/(rms)	B CONTACT	BRONZE	GOLD PLATED	1		
Retention	≥110N	Frequency Range	DC to 6 GHz	C OUTER CONTACT	BRASS	NICKEL PLATED	1+1		
Mechanical lifespan	≥500	Voltage standing wave ratio	<1.30 (DC-3GHz) <1.40 (3GHz-6GHz)	D OUTER CONTACT	ZINC ALLOY	NICKEL PLATED	1		
IP rating	IP67/IP68	Insulation resistance	≥1000V/Ω	E O-RING	EPRM	BLACK	1		
Operation Temperature	-40° C~105° C	Contact resistance	≤5mΩ	F SHIELD	BRASS	NICKEL PLATED	1		
RF Leakage	≥65 dB	Insertion Loss	<0.1x√f (GHz) dB						

**东莞市昌骏电子有限公司**  
Dongguan Changjun Electronics Co., Ltd

SMB矩形母座 线端弯头B1

TITLE:	SMB矩形母座 线端弯头B1		
PART NO.:	CJ-SMB-F11-B1	DRAWING NO.:	CJ-SMB0001
SHEET:	1 / 1	SCALE:	1 : 1
DRAWN:	Xie Junjun	CHECK:	Long Jibang
DATE:		DATE:	2022-01-05

**公差**  
 .xxx ±0.05  
 .xx ±0.10  
 .x ±0.20  
 ±1°

H		F		G	
1	2	3	F	6	1