



Dongguan Changjun Electronics Co., LTD  
 东莞市昌骏电子有限公司

TITLE: 10型快插防水3芯线端母头+塑胶螺母

PART NO: CP-KS1001

SCALE: 1:1

DATE: 2023-04-16

DRAWING NO.: CP-KS1001

REV: A/0

Engagement force	$\leq 40N$	Rated voltage	30V
Disengagement force	$\geq 10N$	Rated current	2A
Mechanical lifespan	$\geq 500$	Insulation resistance	$\geq 1000M \Omega$
IP rating	IP67	Contact resistance	$\leq 10m \Omega$
Flammability	UL94 V-0	Operation Temperature	$-40^{\circ}C \sim 105^{\circ}C$

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	SPECIFY COLOR	1
B CONTACT	BRONZE	GOLD PLATED	3~8
C NUT	PA66+GF	SPECIFY COLOR	1
D O-RING	EPDM	SPECIFY COLOR	1

TOLERANCE	ANGLE
$\pm 0.05$	$\pm 1^{\circ}$
$\pm 0.10$	
$\pm 0.30$	
$\pm 0.50$	

DRAWN: Xie Wenjun CHECK: Long Jichang