



A	3pin	4pin	5pin	
B	图形			
C				
D				
E				
F				
G				
H				
I				
	Engagement force	$\leq 60N$	Rated voltage	250V
	Disengagement force	$\geq 20N$	Rated current	20A
	Mechanical lifespan	≥ 500	Insulation resistance	$\geq 1000M \Omega$
	IP rating	IP67/IP68	Contact resistance	$\leq 20m \Omega$
	Flammability	UL94 V-0	Operation Temperature	$-40^{\circ}C \sim 105^{\circ}C$

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	GOLD PLATED	1
B CONTACT	BRASS	NICKL PLATED	3~5
C OUTER CONTACT	BRASS	NICKL PLATED	1
D O-RING	EPPDM	BLACK	1
E NUT	BRASS	NICKL PLATED	1

Dongguan Changjun Electronics Co., LTD
东莞市昌俊电子有限公司

7/8-16UN2A防水3~5芯线端头 后模面板式M20 S√24T

TITLE:	7/8-16UN2A防水3~5芯线端头 后模面板式M20 S√24T
PART NO.:	CP-M23AXX (3~5)-M01H-M20SM24T
SHEET:	1 / 1
SCALE:	1 : 1
UNIT:	mm
DRAWING NO.:	CP-M230006
SIZE:	A4
REV:	A/0
DRAWN:	Xie Wenjun
CHECK:	Long Jichang
DATE:	2022-11-11