



A	3pin	4pin	5pin	6pin
B	图形			
C				
D				
E				
F				
G				
H				
I				
	Engagement force	≤60N	Rated voltage	250V
	Disengagement force	≥20N	Rated current	20A
	Mechanical lifespan	≥500	Insulation resistance	≥1000M Ω
	IP rating	IP67/IP68	Contact resistance	≤20m Ω
	Flammability	UL94 V-0	Operation Temperature	-40° C~105° C

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	GOLD PLATED	1
B CONTACT	BRASS	NICKL PLATED	3~6
C NUT	BRASS	BLACK	1
D O-RING	EPPDM		1

Dongguan Changjun Electronics Co., LTD
东莞市昌俊电子有限公司

7/8-16UN2A防水30线插头-防振动六角螺母

TITLE: 7/8-16UN2A防水30线插头-防振动六角螺母

PART NO: CJ-M23AH(30)-F02

DRAWING NO.: CP-M230003

SHEET: 1 / 1

SCALE: 1 : 1

UNIT: mm

SIZE: A4

REV: A/0

DRAWN: Xie Wenjun

CHECK: Long Jichang

DATE: 2022-05-27