



由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	GOLD PLATED	1
B CONTACT	BRONZE		5
C NUT	PA66+GF	BLACK	1
D O-RING	SILICA GEL	RED	1

Engagement force $\leq 50N$			
Disengagement force $\geq 15N$			
Mechanical lifespan $\geq 500$			
IP rating IP67/IP68			
Flammability UL94 V-0			
Rated voltage 60V			
Rated current 4A			
Insulation resistance $\geq 1000M\Omega$			
Contact resistance $\leq 20m\Omega$			
Operation Temperature $-40^{\circ}C \sim 105^{\circ}C$			

Dongguan Junhao Interconnection Technology Co., Ltd  
 东莞市俊豪互联科技有限公司

TITLE: M18防水密封螺母-塑胶螺母

PART NO: M18-0002

SCALE: 1:1

UNIT: mm

SIZE: A4

REV: A/0

TOLERANCE	±0.05
	±0.10
	±0.20
	±0.50
ANGLE	±1°
DRAWN:	Xie Wenjun
CHECK:	Long Jichang
DATE:	2019-12-02

1 2 3 4 6 7 8

由 Autodesk 教育版产品制作