



由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作

1	2	3	4	5	6	7	8
Engagement force	≤50N	Rated voltage	250VAC	Rated current	2~8		
Disengagement force	≥5N	Rated current	2~8A	Insulation resistance	1		
Mechanical lifespan	≥500	Insulation resistance	≥1000MΩ	Contact resistance	1		
IP rating	IP67/IP68	Contact resistance	≤10mΩ	Operation Temperature			
Flammability	UL94 V-0	Operation Temperature	-40° C~105° C				

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	GOLD PLATED	1
B CONTACT	BRONZE	NICKEL PLATED	2~8
C NUT	BRASS	NICKEL PLATED	1
D O-RING	EPPDM	BLACK	1

Dongguan Changjun Electronics Co., LTD
东莞市昌骏电子有限公司

TOLERANCE	±0.05	TITLE	M12防水型连接器外壳+10.5L接触螺母
±0.10	±0.20	PART NO.:	DR-1120079
±0.50	±1°	CF-1120079-A-002	DR-1120079
ANGLE	±1°	SCALE:	1:1
		UNIT:	mm
		SIZE:	AA
		REV:	A/0
		DATE:	2022-01-05