



PARTS	MATERIALS	TREATMENT	AMOUNT	
A	HOUSING	PA66+GF	SPECIFY COLOR	1
B	CONTACT	BRONZE	GOLD PLATED	2~8
C	OUTER CONTACT	BRASS	NICKL PLATED	1
D	NUT	BRASS	NICKL PLATED	1
E	O-RING	EPDM	SPECIFY COLOR	1
F				

Dongguan Changjun Electronics Co., LTD 东莞市昌骏电子有限公司				
Engagement force		$\leq 50N$	Rated voltage	2~5pin:60V 6~8pin:30V
Disengagement force		$\geq 5N$	Rated current	2~5pin:4A 6~8pin:2A
Mechanical lifespan		≥ 500	Insulation resistance	$\geq 1000\Omega$
IP rating		IP67/IP68	Contact resistance	$\leq 10m\Omega$
Flammability		UL94 V-0	Operation Temperature	$-40^{\circ}C \sim 105^{\circ}C$
TOLERANCE		.xxx ± 0.05 .xx ± 0.10 .x ± 0.30 x ± 0.50	TITLE: M12防水2~8P线端母头屏蔽款+10L直纹螺母	
ANGLE		$\pm 1^{\circ}$	PART NO.: CJ-M12C(2~8)A-F11	
DRAWN:		Xie Wenjun	DRAWING NO.:	
CHECK:		Long Jichang	CP-M120067	
DATE:		2022-01-05	SHEET: 1 / 1	
			SCALE: 1 : 1	
			UNIT: mm	
			SIZE: A4	
			REV: A/0	