



A		B		C		D		E		F		G		H	
pin位	3pin	4pin	5pin												
图形															
Engagement force	$\leq 50N$			Rated voltage	800V										
Disengagement force	$\geq 10N$			Rated current	16A										
Mechanical lifespan	≥ 500			Insulation resistance	$\geq 1000M \Omega$										
IP rating	IP67/IP68			Contact resistance	$\leq 10m \Omega$										
Flammability	UL94 V-0			Operation Temperature	$-40^{\circ}C \sim 105^{\circ}C$										

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	SPECIFY COLOR	1
B CONTACT	BRASS	GOLD PLATED	3~5
C NUT	BRASS	NICKL PLATED	1
D O-RING	EPDM	SPECIFY COLOR	1
E OUTER CONTACT	BRASS	NICKL PLATED	1

Dongguan Changjun Electronics Co., LTD
东莞市昌骏电子有限公司

TITLE:		M12防水3芯线螺母屏蔽款-C0DF+10L双网纹螺母	
PART NO:	CP-M12E(3.5)K-F-11PB	DRAWING NO.:	CP-M120306
SHEET:	1 / 1	SCALE:	1 : 1
DRAWN:	Xie Wenjun	CHECK:	Long Jichang
DATE:	2023-03-05		

1
2
3
4
5
6
7
8