



Engagement force	$\leq 50N$	Rated voltage	800V
Disengagement force	$\geq 10N$	Rated current	16A
Mechanical lifespan	$\geq 500$	Insulation resistance	$\geq 1000M \Omega$
IP rating	IP67/IP68	Contact resistance	$\leq 10m \Omega$
Flammability	UL94 V-0	Operation Temperature	$-40^{\circ}C \sim 105^{\circ}C$

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	SPECIFY COLOR	1
B CONTACT	BRASS	GOLD PLATED	3~5
C NUT	BRASS	NICKL PLATED	1
D OUTER CONTACT	BRASS	NICKL PLATED	1

Dongguan Changjun Electronics Co., LTD  
**东莞市昌骏电子有限公司**

TITLE:	M12防水3芯线端头屏蔽款-C0DF+10.8L网纹螺丝
PART NO:	CJ-M12E(3)0K-M1P8
DRAWING NO.:	CP-M120308
SHEET:	1 / 1
SCALE:	1 : 1
UNIT:	mm
SIZE:	A4
REV:	A/0
DRAWN:	Xie Wenjun
CHECK:	Long Jichang
DATE:	2023-03-05