



Engagement force	≤50N	Rated voltage	250VAC
Disengagement force	≥5N	Rated current	5A
Mechanical lifespan	≥500	Insulation resistance	≥1000MΩ
IP rating	IP67/IP68	Contact resistance	≤10mΩ
Flammability	UL94 V-0	Operation Temperature	-40° C~105° C

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	GOLD PLATED	1
B CONTACT	BRONZE	NICKEL PLATED	2*8
C OUTER CONTACT	BRASS	NICKEL PLATED	1
D NUT	BRASS	NICKEL PLATED	1
E O-RING	EPDM	BLACK	2

Dongguan Changjun Electronics Co., LTD
东莞市昌骏电子有限公司

TOLERANCE	±0.05	TITLE:	M16*1.5 密封螺母头 后面板式 PG9/M16 5PIN 后插板
XXX	±0.10	PART NO.:	CP-M120020
.XX	±0.20	DRIVING NO.:	
.X	±0.50	SCALE:	1:1
ANGLES	±1°	UNIT:	mm
		SIZE:	AA
		REV:	A/0
		DATE:	2022-01-05

1	2	3	6	7	8
---	---	---	---	---	---