



Engagement force	$\leq 50N$	Rated voltage	30V
Disengagement force	$\geq 10N$	Rated current	2A
Mechanical lifespan	≥ 500	Insulation resistance	$\geq 1000M \Omega$
IP rating	IP67	Contact resistance	$\leq 10m \Omega$
Flammability	UL94 V-0	Operation Temperature	$-25^{\circ}C \sim 105^{\circ}C$

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	GOLD PLATED	1
B CONTACT	BRONZE	BLACK	12
C NUT	ABS	RED	1
D 0-RING	EPDM		1

Dongguan Changjun Electronics Co., LTD
东莞市昌骏电子有限公司

MI6防水12P线端母头-4款+快锁塑胶螺母

TITLE: MI6防水12P线端母头-4款+快锁塑胶螺母

PART NO: CJ-MI6ZXB12A-F01K

SHEET: 1 / 1

SCALE: 1 : 1

DRAWING NO.: CP-MI6Z016

UNIT: mm

SIZE: A4

REV: A/0

DATE: 2023-05-31

DRAWN: Xie Wenjun

CHECK: Long Jichang

TOLERANCE ± 0.05 ± 0.10 ± 0.30 ± 0.50	ANGLE $\pm 1^{\circ}$
---	--------------------------