



Engagement force	$\leq 50N$	Rated voltage	30V
Disengagement force	$\geq 10N$	Rated current	2A
Mechanical lifespan	≥ 500	Insulation resistance	$\geq 1000M \Omega$
IP rating	IP67	Contact resistance	$\leq 10m \Omega$
Flammability	UL94 V-0	Operation Temperature	$-25^{\circ}C \sim 105^{\circ}C$

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	GOLD PLATED	1
B CONTACT	BRONZE	BLACK	12
C NUT	ABS	RED	1
D 0-RING	EPPM		1

Dongguan Changjun Electronics Co., LTD 东莞市昌骏电子有限公司	
TITLE:	M16防水12P线端母头-母款-快锁塑胶螺母
PART NO.:	CJ-M16ZXB12B-F01K
SHEET:	1 / 1
SCALE:	1 : 1
DRAWING NO.:	CP-M16Z017
UNIT:	mm
SIZE:	A4
REV:	A/0

1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---

Engagement force	$\leq 50N$	Rated voltage	30V
Disengagement force	$\geq 10N$	Rated current	2A
Mechanical lifespan	≥ 500	Insulation resistance	$\geq 1000M \Omega$
IP rating	IP67	Contact resistance	$\leq 10m \Omega$
Flammability	UL94 V-0	Operation Temperature	$-25^{\circ}C \sim 105^{\circ}C$

Dongguan Changjun Electronics Co., LTD 东莞市昌骏电子有限公司	
TITLE:	M16防水12P线端母头-母款-快锁塑胶螺母
PART NO.:	CJ-M16ZXB12B-F01K
SHEET:	1 / 1
SCALE:	1 : 1
DRAWING NO.:	CP-M16Z017
UNIT:	mm
SIZE:	A4
REV:	A/0