



Engagement force	$\leq 30N$	Rated voltage	100V
Disengagement force	$\geq 5N$	Rated current	$\leq 3A$
Mechanical lifespan	≥ 200	Insulation resistance	$\geq 1000M \Omega$
IP rating	IP 94 V-0	Contact resistance	$\leq 10m \Omega$
Flammability	UL94 V-0	Operation Temperature	-40° C ~ 105° C

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PBT+GF	GOLD PLATED	1
B CONTACT	BRASS	GOLD PLATED	4
C OUTER CONTACT	BRASS	NICKEL PLATED	1
D HOUSING	PA66+GF	TRANSLUCENT	1
E SHIELD	BRASS	NICKEL PLATED	1
F CONTACT	BRASS	GOLD PLATED	4

东莞市昌骏电子有限公司
Dongguan Changjun Electronics Co., LTD

TITLE: HSD 4P公头 线端插头壳(压接式)

PART NO: G-HEAD-4-011-94

SCALE: 1:1

SIZE: A4

DATE: 2022-01-05

DRAWN: Xie Wenjun

CHECK: Long Jibang

规格	颜色	料号	规格	颜色	料号
A-4-0-11	蓝色	9005	A-4-0-12	白色	7001
B-4-0-11	乳白色	9001	B-4-0-12	石蓝色	4003
C-4-0-11	蓝色	5005	C-4-0-12	米黄色	1001
D-4-0-11	咖啡蓝色	4004	D-4-0-12	咖啡色	1007
E-4-0-11	蓝色	0002	E-4-0-12	黄色	0003
F-4-0-11	咖啡色	0011	F-4-0-12	咖啡色	2003
通用型	蓝色	0011	通用型	咖啡色	0007