



由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作

Engagement force	$\leq 50N$	Rated voltage	24V
Disengagement force	$\geq 10N$	Rated current	2A
Mechanical lifespan	≥ 2000	Insulation resistance	$\geq 1000M \Omega$
IP rating		Contact resistance	$\leq 10m \Omega$
Flammability	UL94 V-0	Operation Temperature	-25° C ~ 85° C

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PBT+GF	BLACK	1
B CONTACT	BRASS	BRIGHT TIN PLATED	3*8
C OUTER CONTACT	BRASS	NICKEL PLATED	1
D			
E			
F			

Dongguan Changjun Electronics Co., Ltd
东莞市昌骏电子有限公司

TITLE: mini DIN 3*8 压接式母端 (全圆压接式)

PART NO: CQ-40 (3*8) -F41

DRAWING NO.: CQ-400020

SHEET: 1 / 1

SCALE: 1 : 1

UNIT: mm

SIZE: A4

REV: A/0

DRAWN: Xie Wenjun

CHECK: Long Jibang

DATE: 2022-01-05

TOLERANCE
 .xxx ±0.05
 .xx ±0.10
 .x ±0.20
 ±0.50
 ANGLE ± 1°