



PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PBT+GF	BLACK	1
B CONTACT	BRASS	GOLD PLATED	10
C OUTER CONTACT	BRASS	NICKEL PLATED	
D		SILVER PLATED	
E		GOLD PLATED	
F		NICKEL PLATED	

Dongguan Changjun Electronics Co., Ltd 东莞市昌骏电子有限公司			
TITLE: mini DIN 10P接触公头 (车针) 四脚单点无耳		DRAWING NO.: CJ-10D0010	
PART NO: CJ-10D10-414		DRAFTING NO.:	
SHEET: 1 / 1		UNIT: mm	
SCALE: 1 : 1		SIZE: REV A/0	
DRAWN: Xie Wenjun		CHECKS: Long Jichang	
DATE: 2022-01-05		DATE:	

Engagement force	Rated voltage	Rated current	Rated power
≤50N	24V	2A	24W
Disengagement force	Rated current	Rated power	Rated power
≥20N	2A	2A	24W
Mechanical lifespan	Insulation resistance	Contact resistance	Operation Temperature
≥2000	≥1000M Ω	≤10m Ω	-25° C~85° C
IP rating	Contact resistance	Operation Temperature	
UL94 V-0	≤10m Ω	-25° C~85° C	
Flammability			