



Engagement force	$\leq 50N$	Rated voltage	24V
Disengagement force	$\geq 20N$	Rated current	2A
Mechanical lifespan	≥ 2000	Insulation resistance	$\geq 1000M \Omega$
IP rating	IP 94 V-0	Contact resistance	$\leq 10m \Omega$
Flammability	UL94 V-0	Operation Temperature	-25° C ~ 85° C

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PBT+GF	BLACK	1
B CONTACT	BRASS	GOLD PLATED	9
C OUTER CONTACT	BRASS	NICKEL PLATED	
D		SILVER PLATED	
E		GOLD PLATED	
F		NICKEL PLATED	

Dongguan Changjun Electronics Co., Ltd
东莞市昌骏电子有限公司

TITLE: mini DIN 中档线端公头 (车针) 圆管插边

PART NO: CJ-409-M21 DRAWING NO.: CJ-400004

SHEET: 1 / 1 SCALE: 1 : 1 UNIT: mm SIZE: REV A/0

DRAWN: Xie Wenjun CHECKS: Long Jichang DATE: 2022-01-05

TOLERANCE
 .xxx ±0.05
 .xx ±0.10
 .x ±0.20
 ANGLES ± 1°