



由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作

Engagement force	≤30N	Rated voltage	250V
Disengagement force	≥50N	Rated current	1.5A
Mechanical lifespan	≥500	Insulation resistance	≥1000MΩ
IP rating		Contact resistance	≤10mΩ
Flammability	UL94 V-0	Operation Temperature	-25° C~85° C

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	RED	1
B CONTACT	BRASS	GOLD PLATED	8
C OUTER CONTACT	BRASS	NICKEL PLATED	1+1
D SHELL	ABS	SPECIFY COLOR	1+1

Dongguan Changjun Electronics Co., LTD
东莞市昌骏电子有限公司

TITLE: **8P双层POWER USB公头 24V (ø5.2)**

PART NO.: **CJ-US90-24V-401-6-2**

DRAWING NO.: **CP-US90001**

TOLERANCE: .xxx ±0.05, .xx ±0.10, .x ±0.20, ANGLES ±1°

SHEET: 1 / 1, SCALE: 1 : 1, UNIT: mm, SIZE: REV A/0

DRAWN: Xie Wenjun, CHECKS: Long Jibang, DATE: 2022-01-05