



PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	RED	1
B CONTACT	BRASS	GOLD PLATED	8
C OUTER CONTACT	BRASS	NICKEL PLATED	1+1
D SHELL	ABS	SPECIFY COLOR	1+1
E			
F			

  

Engagement force	≤30N	Rated voltage	250V
Disengagement force	≥50N	Rated current	1.5A
Mechanical lifespan	≥500	Insulation resistance	≥1000MΩ
IP rating		Contact resistance	≤10mΩ
Flammability	UL94 V-0	Operation Temperature	-25° C~85° C

  

Dongguan Changjun Electronics Co., LTD		TOLERANCE	
东莞市昌骏电子有限公司		.xxx	±0.05
		.xx	±0.10
		.x	±0.20
		∅	±0.30
		ANGLE	± 1°
TITLE: 8P双层POWER USB公头 24V(ø6.5)		PART NO.:	DRAWING NO.:
CJ-US8-24V-001-6-5		CJ-US8-24V-001-6-5	CP-US80002
SHEET: 1 / 1		SCALE: 1 : 1	UNIT: mm
DRAWN: Xie Wenjun		CHECKS: Long Jibang	SIZE: REV
DATE: 2022-01-05			A/0

由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作